

ARCHITECTURAL & BUILDING STAND ALONE USE

The complete range of stand alone DMX interfaces.



SLESA-IP1
IP Version



SLESA-U9
Entry level USB



NEW!
256
CHANNELS



SLESA-U8
USB Version



SLESA-UE7
USB-Ethernet Version




NEW!
USB +
ETHERNET



STICK-GU2
Glass Touch Sensitive
Control Keypad

NEW!
8X MORE
MEMORY



STICK-GA2
Glass Touch Sensitive
Control Keypad

COMPUTER

USB connection		•	•	•	•	•
Ethernet connection	•			•		
Internet connection	•			•		
Easy Stand Alone software (ESA)	•	•	•	•	•	•
Easy Stand Alone 2 software (ESA2)		•	•	•	•	•
ESA Pro software				•		
Arcolis App				•		

STAND ALONE

DMX channels	512	256	512	2x512	128	512
Number of scenes	255	20	255	250	24	99
Number of zones	1	1	1	5	1	1
Stand Alone memory	128K	20K	128K	microSD	12K	76K
Memory capacity with 20 channels	5629	1200	5600	Unlimited	840	3200
Memory capacity with 60 channels	2109	440	2100	Unlimited	310	1200
Memory capacity with 512 channels	259		240	Unlimited		140
Power voltage	9V-12V DC 300mA	5V-16V DC 300mA	5V-10V DC 300mA	5V-10V DC 300mA	5V-16V DC 300mA	5V-16V DC 300mA
Power connector	Round 2,1mm	mini USB	mini USB	mini USB	Connector block	Connector block

TRIGGERING

Mechanical buttons	3	3	3	3		
Touch-sensitive buttons					3	4
Internal connector		18 pins	HE10	HE10		
Ports triggering	8	8	8	8	1	8
Clock triggering	20		100	100		
Infrared remote control					•	
RS232 triggering					For RS232 triggering	see STICK-KE1 or STICK-DE3
Smartphone/Tablet control					•	For PHONE/TABLET control see STICK-KE1 or STICK-DE3

* Some UE7 features released throughout 2013