

STICK RANGE 4 PRODUCTS

The STICK range has been designed to offer the perfect lighting control solution for any environment. From the sophisticated STICK-GU2 and STICK-GA2 up to the powerful network functionality of the STICK-DE3 and STICK-KE1, each STICK has been tailored to meet everyone's needs.

	STICK-GU2	STICK-GA2	STICK-DE3	STICK-KE1	
General	Design	Glass	Glass	Glass	Plastic
	Dimensions	86 x 86 x 11 mm	86 x 110 x 11 mm	106 x 146 x 11 mm	130 x 170 x 11 mm
	Weight	130g	160g	250g	200g
	USB connection	•	•	•	•
	Ethernet connection			•	•
	DMX channels	128	512	2x512	2x512
	SD card			MicroSD card	MicroSD card
Software	ESA software	PC	PC	PC	PC
	ESA2 software	PC / Mac	PC / Mac	PC / Mac	PC / Mac
	ESA Pro software			PC	PC
	DMX recorder software			PC	PC
	DMX Lightpad app			iOS / Android	iOS / Android
	Arcolis app			iOS / Android	iOS / Android
Stand Alone	Number of scenes	24	99	500	200
	Number of zones	1	1	10	5
	Memory capacity (steps) with 20 chan.	840	3200	SD card limit	SD card limit
	Memory capacity (steps) with 60 chan.	310	1200	SD card limit	SD card limit
	Memory capacity (steps) with 512 chan.		140	SD card limit	SD card limit
	Power voltage	5V-12V DC	5V-12V DC	5V-6V DC	5V-6V DC
	Power connector	Screw terminal block	Screw terminal or RJ45	Screw terminal or RJ45	Screw terminal block
Triggering	Live control	Color / Dimmer	Color / Dimmer	Color / Dimmer / Speed	Color / Dimmer / Speed
	Touch-sensitive buttons	3	4	20	22
	Port triggering	1	8	8	8
	Clock triggering			100	40
	RS232 triggering			•	•
	Audio triggering				KU1 only
	Infra Red triggering				•
Optional	AC/DC adapter (not included)	Ref. POWER4M	Ref. POWER4M	Ref. POWER4M	Ref. POWER4M
	IR remote control (not included)				Ref. IR-REMOTE
	RJ45 to CONNECTOR BLOCK board		Ref. RJ2BLOCK	Ref. RJ2BLOCK	