

Data Sheet

Item No. S5050-LED-RGBWP

Low Cost LED RGB Strip 5050 SMD 5m 16.4ft | Single 30LED/m IP67

LED INFO ON LED STRIP

LED Density	9 /ft - 30 /m
LED Count (Total)	150 Per Reel
LED Type	Selected 5050 SMD
LED Ambience Operating Temperature	-50° - 165° F

POWER*

Working Voltage / Input Voltage / Voltage Forward	12V DC
Power Consumption (Watts) <i>Max.</i>	1.46 W/ft - 4.80 W/m - 24 W/5 m Reel
Current Draw / Input Current / Current <i>Max.</i>	2000 mA - 2.0 A - 5 m Reel
Power Drop Along The Strip (Meter) <i>Approx.</i>	1 m 5% - 5 m 25%

PHOTOMETRY

Light Color	RGB - Red, Green, Blue - 16 Million Colors Posibles
Peak Wave Length (nm)	Red 625/ Green 524/ Blue 471
Brightness (Lumen)	66 lm/ft - 216 lm/m - 1082 lm/Reel (5 m)
Beam Angle (Degree)	120°
UV/IR Emission	None
Lifespan / Average Lifetime / Lumen Maintenace	40,000 - 60,000 Hours (50% Brightness Loss)

DIMENSIONS

Reel Total Length (Feet - Meter)	16.4 ft - 5 m
LED Spacing Between Centers (Inches - Milimeters)	1.31 in - 33.30 mm
LED Spacing Between Edges (Inches - Milimeters)	1.11 in - 28.20 mm
Minimum Cuttable Segments (Inches - Milimeters)	3.94 in - 100 mm (3 LED)
Width (Inches - Milimeters)	0.50 in - 12.70 mm
Height (Inches - Milimeters)	0.175 in - 4.45 mm
Cable Leads (Inches - Milimeters)	7 in - 178 mm
LED Strip Dimension Drawing	

LED STRIP INFORMATION

LED Strip IP Rating	Waterproof IP67
LED Strip Adhesive	High Quality 3M Adhesive
LED Strip Finish Color / Product Color	White
LED Strip Weight (Without Packaging Material)	6.6 oz. - 187 g
LED Strip Warranty	30 Days Limited

PRODUCT COUNTRY OF ORIGIN

QC Quality Control	China
Product Engineering & Design	China
Assembled	China
Technical Support	USA
Product Customization	USA Available

INSTALLATION MATERIALS & ASSOCIATED PROD.

Dimming and Color Mixing Options	DMX, Radio Frequency (RF), Infrared (IR), & Analog
Max Length in One Run for Linear Lighting	Unlimited Thru .Amplifiers or DMX Controllers
Power Supply	Options Available
DMX Programming & Stand Alone	Options Available
LED RGB Strip Connectors	Options Available
Installation Cable 4 Wires	Options Available
Installation Cable 2 Wires	Options Available
Installation Accessories	Options Available
Installation Kits	Soldering Kit, Heashrink Kit, Silicone Tube

(*) NOTES

- The Power Rating has been measured with the strip power in both ends
- A good technique to minimize voltage drop and increase lumens output is to power the strip on both ends.
- LED electrical and optical characteristics change with the die manufacturing date.
- LED performance and life span is affected by environmental conditions, manufacturing techniques and actual components characteristics.
- We reserve the right to change any data without prior notice.

Segment Close Up and Dimensions

