


Item No. 5050-24WW-3067			
LED Warm White Strip 5050 SMD White 5m 16.4ft Single Density 30 LED/m IP67			
LED INFO			
LED Density	9 /ft	30 /m	
LED Count (Total)	150 Per Reel		
LED Type	High Quality Selected 5050 SMD White		
LED Ambience Operating Temperature	-20°F to 120°F		
LED Storage Temperature	-13°F to 140°F		
POWER*			
Working Voltage / Input Voltage / Voltage Forward	24V DC		
Power Consumption (Watts) Max.	2.56W /ft	8.413W /m	42.05W /5m Reel
Current Draw / Input Current / Current Max.	1752mA	1.752A	per 5m Reel
Power Drop Along the Strip (V+ In One Side) Approx	1m = 3%	5m = 5%	
Power Drop with <u>V+</u> <u>In</u> on Both Sides Approx.	1m = 1%	5m = 2%	
PHOTOMETRY			
Light Color	Warm White - 3,000 °K		
Peak Wave Length (nm) Approx.	N/A		
Brightness (Lumen) Tested in all colors at full intensity	299 lm/ft	982 lm/m	4908 lm/Reel (Approx.)
Beam Angle	120°		
UV/IR Emission	None		
Lifespan / Average Lifetime / Lumen Maintenance	50,000 - 75,000 Hours (50% Brightness Loss)		
DIMENSIONS			
Reel Total Length	16.4ft	5m	
LED Spacing Between Centers (Inches Millimeters)	1.31in	33.25mm	
LED Spacing Between Edges (Inches Millimeters)	1.11in	28.15mm	
Minimum Cuttable Segments (Inches Millimeters)	6.57in	167mm (Every 5 LEDs)	
Width (Inches Millimeters)	0.50in	12.7mm	
Height (Inches Millimeters)	0.18in	4.45mm	
Cable Leads (Inches Millimeters)	12in	304.8mm	
LED STRIP INFORMATION			
LED Strip IP Rating	Waterproof IP67		
LED Strip Adhesive	High Quality 3M Adhesive		
LED Strip Finish Color / Product Color	White		
LED Strip Net Weight (Without Packaging Material)	7.9 oz	224.0 g	
LED Strip Warranty	3 Years Limited		
UL Certification	UL Listed; UL 2108; E479339		

Item No. 5050-24WW-3067 (Continued)	
LED Warm White Strip 5050 SMD White 5m 16.4ft Single Density 30 LED/m IP67	
PRODUCT COUNTRY OF ORIGIN	
QC Quality Control	USA
Product Engineering & Design	USA
Assembled	China Preassembly / USA Final Assembly
Technical Support	USA
Product Customization	USA
INSTALLATION MATERIALS & ASSOCIATED PRODUCTS	
Dimming and Color Mixing Options	DMX, Radio Frequency (RF), Infrared (IR), & Analog
Max Length in One Run for Linear Lighting	Unlimited Thru Amplifiers or DMX Controllers
Power Supply	Options Available
DMX Programming & Stand Alone	Options Available
LED RGB Strip Connectors	Options Available
4 Wire Installation Cables	Options Available
2 Wire Installation Cables	Options Available
Installation Accessories	Options Available
Installation Kits	Soldering Kit, Heatshrink Kit, Silicone Tube

(*) NOTES

- The Strip Power Rating was measured with power input on both ends
- A good technique to minimize voltage drop and increase lumen output is to power the strip on both ends.
- LED electrical and optical characteristics change with the die manufacturing date.
- LED performance and life span is affected by environmental conditions, manufacturing techniques, and actual component characteristics.
- We reserve the right to change any data without prior notice.

Segment Close Up and Dimensions



Item No.
5050-24WW-3040
5050-24WW-3067

Front View

