

Item No. 5050-LED-WWWP			
LED Warm White Strip 5050 SMD 5m 16.4ft   Single Density 30LED/m IP67			
LED INFO ON LED STRIP			
LED Density	9 /ft	30 /m	
LED Count (Total)	150 Per Reel		
LED Type	High Quality Selected 5050 SMD		
LED Ambience Operating Temperature	-20°F to 120°F		
LED Storage Temperature	-13°F to 140°F		
POWER*			
Working Voltage / Input Voltage / Voltage Forward	12V DC		
Power Consumption (Watts) <i>Max.</i>	2.12 W /ft	6.96 W /m	34.80 W/ 5m Reel
Current Draw / Input Current / Current <i>Max.</i>	2900mA	2.90A	5m Reel
Power Drop Along the Strip (Meter) <i>Approx.</i>	1m = 6%	5m = 13%	
PHOTOMETRY			
Light Color	Warm White - 2,950°K		
Brightness (Lumen)	272 lm/ft	892 lm/m	4462 lm/Reel <i>(Approx.)</i>
Beam Angle	120°		
UV/IR Emission	None		
Lifespan / Average Lifetime / Lumen Maintenance	50,000 to 75,000 hours		
DIMENSIONS			
Reel Total Length	16.4ft	5m	
LED Spacing Between Centers (Inches   Millimeters)	1.31in	33.30mm	
LED Spacing Between Edges (Inches   Millimeters)	1.11in	28.20mm	
Minimum Cuttable Segments (Inches   Millimeters)	3.94in	100mm (3 LEDs)	
Width (Inches   Millimeters)	0.50in	12.70mm	
Height (Inches   Millimeters)	0.175in	4.45mm	
Cable Leads (Inches   Millimeters)	7in	178mm	
LED STRIP INFORMATION			
LED Strip IP Rating	Waterproof IP67		
LED Strip Adhesive	High Quality 3M Adhesive		
LED Strip Finish Color / Product Color	Copper		
LED Strip Weight (Without Packaging Material)	6.6 oz	187.11g	
LED Strip Warranty	1 Year Limited		

Item No. 5050-LED-WWWP(Continued)	
LED Warm White Strip 5050 SMD 5m 16.4ft   Single Density 30LED/m IP67	
<b>PRODUCT COUNTRY OF ORIGIN</b>	
QC Quality Control	USA
Product Engineering & Design	USA
Assembled	China
Technical Support	USA
Product Customization	USA
<b>INSTALLATION MATERIALS &amp; ASSOCIATED PRODUCTS</b>	
Dimming and Color Mixing Options	DMX, Radio Frequency (RF), Infrared (IR), & Analog
Max Length in One Run for Linear Lighting	Unlimited Thru Amplifiers or DMX Controllers
Power Supply	Options Available
DMX Programming & Stand Alone	Options Available
LED RGB Strip Connectors	Options Available
4 Wire Installation Cables	Options Available
2 Wire Installation Cables	Options Available
Installation Accessories	Options Available
Installation Kits	Soldering Kit, Heatshrink Kit, Silicone Tube

**(\*) NOTES**

- Due to our constant revisions/upgrades of our line of White LED Strips, lumen output increases with every generation
- The Strip Power Rating was measured with power input on both ends
- A good technique to minimize voltage drop and increase lumen output is to power the strip on both ends.
- LED electrical and optical characteristics change with the die manufacturing date.
- LED performance and life span is affected by environmental conditions, manufacturing techniques, and actual component characteristics.
- We reserve the right to change any data without prior notice.

**Segment Close Up and Dimensions**

